

# Technical data sheet

FOR THE ROTARY ACTUATOR

Type: HSE 07 SZ  
Art. no.: 4104935

Model .....	Vane-type rotary actuator In principle the actuation has a pressure- and viscosity-dependent internal leak volume flow rate. For example, if an external torque affect the rotary actuator shaft in an idle mode, the rotary actuator shaft shifts slowly from its angle position!
Series .....	HSE: Rotary actuator with end position damping and with or without rotary angle limitation.
Size .....	07
Mounting style	
- Rotary actuator housing .....	single-sided face mounting with thread according to DIN 13-1 - M 16 Strength class of the fastening screws $\geq 8.8$
- Drive shaft end .....	involute spline shaft according to DIN 5480-W 95x3,0x30x 8f
- Centre hole in the drive shaft end .....	DIN 332-2 - D M 24
Connection type .....	pipe thread according to DIN ISO 228-1; A and B: G1/2; axial in the end-position damping block
Installation position .....	arbitrary; Depending on the position of installation and case of application a load may cause running ahead the rotary actuator drive shaft. In such a case, appropriate countermeasures must be taken!
Installation instructions .....	see operating instructions
Rotary angle limitation .....	An external rotary angle limitation is recommended!
Intended use .....	The rotary actuator is intended for generation an alternating torque in a stationary application.

max. nominal pressure	$p_{N \max}$	bar	160		1)
min. minimum pressure	$p_{M \min}$	bar	20	Required for a proper functioning of the load-free drive.	
max. starting pressure without load	$p_{St \max}$	bar	8.0	at an output pressure of $p = 1 \text{ bar}$	
specific torque	$M_{sp}$	Nm/bar	55.13	torque constant	2)
theoretical torque	$M_{th}$	Nm	8 821	at $\Delta p = p_{N \max}$	2)
mechanical efficiency $\approx$	$\eta_{mec}$	-	0.950	at $\Delta p = p_{N \max}$ and $\omega = \omega_{\max}$	3)
effective torque	$M_{eff}$	Nm	8 380	at $\Delta p = p_{N \max}$ and $\omega = \omega_{\max}$	3)
number of working chambers	Z	-	2		
nominal angle of rotary	$\varphi_N$	grad	282	The internal stop must not be approached!	2)
max. operating angle of rotary	$\varphi_{A \max}$	grad	280		
recom. min. operating angle of rotary	$\varphi_{A \min}$	grad	20	If smaler rotating angles are to be realised in continious operation, the manufacturer must be consulted.	
maximum radial force	$F_{r \max}$	N	15 000	force acting centered on the journal of the drive shaft	
maximum axial force	$F_{ax \max}$	N	7 500	force acting centrically on the journal of the drive shaft	
weight $\approx$	m	kg	131.0	$\pm 10\%$ , incl. oil filling	
mass moment of inertia of drive shaft	$J_{W0}$	kgdm <sup>2</sup>	9.96	$\pm 5\%$ , without other attachments such as hub, coupling, rotation encoder, etc.	
max. angular speed	$\omega_{\max}$	rad/s	2.5	This corresponds to 143 deg/s or an equivalent rotational speed of $n = 24 \text{ min}^{-1}$ .	1)
specific displacement	$V_{sp}$	cm <sup>3</sup> /°	9.62	This results in a theoretical operating volume of $V_A = 2 694.2 \text{ cm}^3$ .	2)
theoretical volume flow rate required	$Q_{th}$	l/min	82.7	at $\omega = \omega_{\max}$	2)
max. internal leakage volume flow rate	$Q_{L \max}$	l/min	0.46	at $\Delta p = p_{N \max}$ and $v = 50 \text{ mm}^2/\text{s}$	3)4)
effective required volume flow rate	$Q_{eff}$	l/min	83.2	at $\Delta p = p_{N \max}$ , $\omega = \omega_{\max}$ and $v = 50 \text{ mm}^2/\text{s}$	3)4)
permissible pressure fluid				HLP mineral oils according to DIN 51524 T2	
temperature range of pressure fluid	$\vartheta_{oi}$	°C	-20 – +80	The viscosity range set in operation is to be observed.	1)
range of kinematic viscosity	$\nu$	mm <sup>2</sup> /s	18 – 150	short-term, the optimum operating viscosity range is 30 – 50 mm <sup>2</sup> /s	
cleanliness class of pressure fluid				Max. permissible degree of pollution according to ISO 4406 class 18/16/13. To increase service life, we recommend according to ISO 4406 class 17/15/12.	
range of ambient temperature	$\vartheta$	°C	0 – +60		
design of component surfaces				metallic bright and wetted with anticorrosion agents Subject to technical modifications and error!	

1) The simultaneous occurrence of two or more maximum values of temperature, pressure and angular speed requires the written consent of the manufacturer!

2) Theoretically determined value without manufacturing tolerances and if so an efficiency.

3) Median recorded in test series; an inferential variance is possible.

4) In mint condition of the internal seals and their counter-surfaces!